

SPECIFICATIONS - PLATE SHEAR FEEDER

TABLE

- 66" wide x 186" long made from 4" x 4" x 3/16" hollow structural tubes with 6 legs complete with floor levelling screws. Suitable for plates up to 20' long. Capacity 5,000 lbs.
- 30mm ball transfers set in hardened recessed holders spaced approximately 14" staggered centers, capacity 2,000 lbs. each

DRIVE WHEELS

- 6 - 6" diameter hard urethane wheels, hydraulically driven with variable speed control, forward and reverse, pneumatically controlled for upward pressure, 3" maximum lift, each wheel lifts independently to match bowed or bent plates

CONTROLS

- Pedestal mounted, consists of hydraulic forward/reverse/jog joystick, up/down pneumatic lever control for wheels and variable pneumatic pressure control with gauge

SQUARING PINS

- 3 hardened steel squaring pins, adjustable for 4' to 10' wide plate, mounted to frame with heavy steel alignment screws to maintain plates square with shear blade and provide easy re-adjustment.

AIR SUPPLY

- clean dry air of 100 psi, 5 cu. ft./min. minimum required from customer with air line to our 3/4" inlet on filter, lubricator, regulator unit

POWER PACK

- 3/4 H.P. hydraulic motor, pump and reservoir, requires 120V, 575V or 480V power supply from customer

OPTIONS

- 66" wide x 120" long table with 4 only drive wheels suitable for handling plates up to 16' maximum length
- Multiple strand plate top chain conveyor with 4 rows of material support arms and optional scrap chute
- Multiple strand plate top chain conveyor with 4 rows of material support arms with extended length conveyor with center lift table to handle cutting large pieces from 20' to 40' plates
- Portable multiple pallet stacker to connect to conveyor and stack up to 60" wide blanks on skids or runners